

Professional

TT 550



- Auto Start
- Soft Start
- Peristaltic detergent & rinse aid pumps
- Drain pump Standard
- Adjustable water temperature
- 70°F rise booster
- Single Piece deep Drawn Tank
- guaranteed sanitizing rinse cycle (190°F)
- Durable Stainless Steel Detergent injection port
- Insulated Double wall construction (0.32" SS)
- 304 Stainless Steels exterior
- Independant upper and lower wash and rinse arms
- Particle trap sensor
- Durable Flexible hoses supplied
- 2 Dish racks Supplied
- Maintains functionality under error conditions
- External Heating element

WAREWASHERS

TECHNICAL DATA		TT 550
Rack Dimensions	In.	20 X 20
Usable opening Height	In.	15.2
Tank capacity	Gal.	3
Dimensions (width x depth x height)	In.	24 X 25 X 32
Max Power	KW	6.9
Quick Cycle	sec	60
Standard Cycle	sec	110
Intensive Cycle	sec	150
Continuous wash		yes
Max output	Plates/hr	1.080
Water Feed	°F	59°-131°
Tank Temperature	°F	158
Boiler Temperature	°F	190
Tank Capacity	Gal.	3.17
Boiler Capacity	Gal.	0.92
Water Consumption	Gal	0.78
Voltage	V/PH/Hz	240/1/60
Fill water temperature	°F	122
Fill water pressure	Bar	1-4
Fill hose connection		G3/4" M
Drain hose diameter	In.	0.98

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



